

PVD COATED STAINLESS

CARE AND MAINTENANCE SHEET

CONTACT

09 828 1814

architectural@ambrometals.com

www.ambrometals.com

Produced through the process of Physical Vapour Deposition Titanium Ion Plating. Enhance resistance towards accumulating wear, scratch, and corrosion. This method is far more enduring than conventional coating methods, such as electroplating or powder-coating.

Guidelines to extend your care for PVD coatings:

ADDRESS

14 Timothy Place
Avondale, 0604
Auckland, New Zealand
PO Box 15599

- Handle with clean gloves or cloths to guard against fingerprints and stains. Fingerprints can be removed by washing products with a mild soap and water solution, then dried.
- Clean occasionally with a soft, dry cloth or duster.
- Wash periodically with a soft cloth and mild soap water followed by drying with a clean, soft cloth.
- In the case of a softer metal, such as a ring or key, scratches the surface, it is possible some of this metal may have been left on the PVD coated surface. In this case a soft cloth and mild, non-acidic cleaner must be used to remove soft metal deposit.
- Rub/wipe in direction of polish lines, not across.
- DO NOT apply oily rags or greasy cloths when wiping product surface.
- DO NOT apply bleach, caustic, or acid-based cleaning materials. This includes detergents containing chloride and other harsh household cleaning products.
- Do NOT apply scouring powder.
- DO NOT apply abrasive materials, files, or other hard objects against PVD stainless steel surface.